

# COMMERCIAL & RESIDENTIAL FILM

## SPUTTERING NSN 60

### ◆ SPECIFICATION

<b>Total Solar Energy</b>	<b>Transmission</b>	<b>35%</b>
	<b>Reflection</b>	<b>31%</b>
	<b>Absorbed</b>	<b>34%</b>
<b>Visible Light</b>	<b>Transmission</b>	<b>56%</b>
	<b>Reflection</b>	<b>28%</b>
<b>UV Rejection</b>		<b>99%</b>
<b>Shading Coefficient</b>		<b>0.52</b>
<b>Total Solar Energy Rejection</b>		<b>58%</b>
<b>Heat Transmission (W/m<sup>2</sup>K)</b>		<b>5.6</b>
<b>Structure</b>		<b>2PLY</b>
<b>Thickness</b>		<b>2MIL</b>
<b>Standard Widths [mm(inch)]</b>		<b>1,524 (60") / 1,830 (72")</b>



## NTECH WINDOW FILM

3F, SUNAM B/D, YANGPYUNG DONG, 1-GA, YOUNGDENGPOGU, SEOUL, KOREA

TEL: 82-2-786-3479 FAX: 82-2-782-9284 E-MAIL: [ntech@ntechgood.com](mailto:ntech@ntechgood.com)